

# CertainTeed Sand Micro™

## Performance Series Mineral Fiber Ceilings

### Features:

- Special pulverized-marble aggregate coating provides rugged durability.
- Offers upscale look with additional durability and resists sagging.
- Designed for conditions where high temperatures and high humidity exist.
- Lightly textured surface provides attractive finish with excellent light reflectance and durability.
- Micro perforated for sound absorption.

See reverse side for additional product specifications.



ITEM NUMBER	NOMINAL SIZE (Inches)	EDGE DETAIL	UL CLASSIFIED		LR	RECYCLED CONTENT %
			NRC	CAC		
<b>SAFETONE® CLASS A</b>						
SHM-150	24 x 24 x 5/8	Narrow Reveal	.50	35	.87	52-62
SHM-150M	600 x 600 x 15mm	Narrow Reveal	.50	35	.87	52-62
SHM-154	24 x 24 x 5/8	Reveal	.50	35	.87	52-62
SHM-154M	600 x 600 x 15mm	Reveal	.50	35	.87	52-62
SHM-157	24 x 24 x 5/8	Trim	.50	35	.87	52-62
SHM-157M	600 x 600 x 15mm	Trim	.50	35	.87	52-62
SHM-190	24 x 48 x 5/8	Narrow Reveal	.50	35	.87	52-62
SHM-190M	600 x 1200 x 15mm	Narrow Reveal	.50	35	.87	52-62
SHM-194	24 x 48 x 5/8	Reveal	.50	35	.87	52-62
SHM-194M	600 x 1200 x 15mm	Reveal	.50	35	.87	52-62
SHM-197	24 x 48 x 5/8	Trim	.50	35	.87	52-62
SHM-197M	600 x 1200 x 15mm	Trim	.50	35	.87	52-62

ASTM E 1264 Classification: Type III, Form 2, Pattern C E

### Popular Applications:


- Education • Retail • Malls • Offices • Healthcare
- Restaurants • Airports • Reception Areas




**BioShield™**  
BioShield™ treatment included for added mold and mildew resistance.




### Edge Details:




**TRIM EDGE**  
(Square) 1/8" Grid



**REVEAL EDGE**  
(Beveled) 1/8" Grid



**NARROW REVEAL EDGE**  
(Corner Bevel) 1/8" Grid



**NARROW REVEAL EDGE**  
(Corner Bevel) 1/8" Grid (Bolt Slot)

# PRODUCT SPECIFICATION DETAILS

## ACOUSTICAL CEILINGS

### 09 51 00

---

## PART 2: PRODUCTS


### 2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

### 2.2 MATERIALS

Acoustical Ceiling Units:

#### Standard Sizes:



1. Type III
2. Form 2
3. Pattern C E
4. Micro perforated wet-felted lay-in panel
5. Size [5/8"] [15mm] thick x [24"x 24"] [24"x 48"] [600x600mm] [600x1200mm]
6. Edge Detail [Trim (Square)] [Narrow Reveal (Corner Bevel)] [Reveal (Beveled)]
7. Noise Reduction Coefficient (NRC) .50
8. Ceiling Attenuation Class (CAC) 35
9. Light Reflectance Coefficient (LR) .87  
Light Reflectance Designation LR-1
10. Color White
11. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
12. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
13. Product Name Sand Micro™

---

Distributed by:

## ASK ABOUT OUR OTHER CERTAINTEED PRODUCTS AND SYSTEMS:

**EXTERIOR:** ROOFING • SIDING • WINDOWS • FENCE • RAILING • TRIM • DECKING • FOUNDATIONS • PIPE  
**INTERIOR:** INSULATION • WALLS • CEILINGS

---

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777  
[www.certainteed.com](http://www.certainteed.com)

**CertainTeed** 

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. CertainTeed assumes no responsibility for the effects of structural movement.

™ © CertainTeed and the tag line "Quality made certain. Satisfaction guaranteed." are trademarks of CertainTeed Corporation. All other trademarks are the property of its affiliates and related companies.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

©02/07 CertainTeed Corporation. Printed in U.S.A. CTC-4869/W/04-2007