



When ceiling installers design your product, everything just **clicks.**

© 2017 CertainTeed Corporation

QUICKSPAN™ LOCKING DRYWALL GRID SYSTEM

FASTER PRODUCTION, LOWER LABOR COST

In hands-on trials, installers agree – the click-in design of QuickSpan delivers faster installation with strength and stability.

LONGEST UNSUPPORTED SPANS

With the highest tested and certified load data, QuickSpan spans more distance without mid-span support or hanger wire.



FAST Cross tees lock into channel, no screws needed



SIMPLE Convenient pre-measured tabs make layout a breeze



SMART Audible click lets you know cross tee is locked in place



SOLID No rolling or deflection when attaching drywall

CertainTeed
SAINT-GOBAIN
Ceilings



“Easy to use. And quick. It’s all you could ask for”

– Jim C., carpenter & ceiling specialist for 30 years

“This is a superior product”



– John, carpenter & ceiling specialist for 23 years

ANOTHER TIME-SAVING SOLUTION FROM CERTAINTEED.

Quicker, easier spans for drywall ceilings in hallway/corridor applications



QUICKSPAN™ LOCKING DRYWALL GRID SYSTEM




QUICKSPAN CROSS TEE

- Eliminates need for hanger wires for longer unsupported spans (see chart below)
- Knurled face for better screw bite
- Heavy-duty material for maximum rigidity and screw grip
- Standard and custom lengths available
- Tested performance data available in ICC ESR-3941

APPLICATIONS

- Condominiums / Apartments
- Hotels / Motels
- Education
- Healthcare
- Offices



QUICKSPAN LOCKING CHANNEL

- Pre-engineered locking tabs punched 8" on center
- Tees quickly twist into place for fast installation
- Positive click confirms tee is locked
- Locking tab prevents lateral and upward movement (deflection)
- 10 year limited warranty

QUICKSPAN. THE LONGEST UNSUPPORTED SPANS YOU CAN GET.

MAX CLEAR SPAN LOAD FOR 2.5 LBS./SF (5/8" BOARD)	8" O.C.	11' 3" (135.6")	MAX CLEAR SPAN LOAD FOR 2.0 LBS./SF (1/2" BOARD)	8" O.C.	12' (144")
	16" O.C.	9' (107.7")		16" O.C.	9' 8" (116")
	24" O.C.	7' 7" (91.1")		24" O.C.	8' 2" (98.2")

MAX CLEAR SPAN LOAD FOR 1.4 LBS./FT2 (LIGHTWEIGHT 1/2" BOARD)	8" O.C.	12' (144")
	16" O.C.	10' 10" (130.6")
	24" O.C.	9' 6" (114.1")

*CertainTeed Easi-Lite™ Drywall boards weigh between 1.2 and 1.4 lbs/SF.

SEE OUR ENTIRE LINE OF DRYWALL GRID SYSTEMS AT CERTAINTEED.COM/QUICKSPAN OR CALL 800-233-8990

CertainTeed.com/QuickSpan 800-233-8990

© 04/17 CertainTeed Corporation

CTC-06-500

CertainTeed
SAINT-GOBAIN
Ceilings