

SERENO™ FINE FISSURED

Fissured
Mineral Fiber

Experience faster installations and higher acoustic performance with Sereno Fine Fissured.




APPLICATIONS

- Universities
- Public Schools
- Healthcare Spaces
- Open Plan Offices
- Corridors
- Areas with HVAC Noise Concerns
- Libraries / Media Centers
- Computer Rooms
- Other Commercial Buildings / Space Applications

FEATURES AND BENEFITS

- Superior acoustical combination provides high in-room sound absorption with room-to-room sound blocking capabilities for privacy
- Cuts quickly and cleanly with minimal dust for cost-efficient installation
- Attractive non-directional fissured pattern to aid in quick installation
- Complies with LEED v4 for Schools classroom acoustics prerequisite
- Meets ANSI S12.60 classroom acoustic guidelines
- Environmental Product Declaration (EPD) available
- Health Product Declaration (HPD) available
- High USDA Certified Biobased content at 98%


SUSPENSION SYSTEM OPTIONS




Trim
15/16 Grid



Revealed
Beveled
15/16 Grid



Narrow Revealed
Corner Bevel
9/16 Grid



Narrow Revealed
Corner Bevel
9/16 Grid Bolt Slot

LEED® v4

RECYCLED CONTENT 70%

<input type="checkbox"/>	EA: Optimize Energy Performance
<input type="checkbox"/>	EA: Prereq. Min. Energy Performance
<input type="checkbox"/>	EQ: Interior Lighting
<input checked="" type="checkbox"/>	MR: PBT Source Reduction (Healthcare)
<input checked="" type="checkbox"/>	EQ: Acoustic Performance
<input checked="" type="checkbox"/>	EQ: Prereq. Min. Acoustic Performance (Schools)
<input checked="" type="checkbox"/>	EQ: Low-Emitting Materials
<input checked="" type="checkbox"/>	EQ: Daylight
<input checked="" type="checkbox"/>	MR: Material Ingredients (HPDs)
<input checked="" type="checkbox"/>	MR: Sourcing Raw Materials
<input checked="" type="checkbox"/>	MR: Environmental Product Declarations (EPDs)
<input checked="" type="checkbox"/>	MR: Construction and Demolition Waste Management Planning



EPD Available



HPD Available



SERENO™ FINE FISSURED

Fissured
Mineral Fiber

All products in this line
feature these attributes:



SAG
RESISTANT



BIOSHIELD™
MOLD/MILDEW
RESISTANT



LR
0.83



EPD
AVAILABLE



HPD
AVAILABLE



LOW
VOC
EMISSION
COMPLIANT
CERTIFIED



RECYCLED
CONTENT
70%

SERENO FINE FISSURED		Format	Dimensions (in.)	NRC	CAC	Recycled Content	UL Fire-Rated	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet	
TRIM												
	NRC 75	SFF-457 HNRC/HCAC	Panels	24 x 24 x 3/4	0.75	40	70%	—	12	48	52	20
		SFF-497 HNRC/HCAC	Panels	24 x 48 x 3/4	0.75	42	70%	—	6	48	52	20
REVEAL												
	NRC 70	SFF-454 HNRC/HCAC	Panels	24 x 24 x 3/4	0.70	40	70%	—	12	48	54	20
		SFF-494 HNRC/HCAC	Panels	24 x 48 x 3/4	0.70	42	70%	—	6	48	54	20
NARROW REVEAL												
	NRC 75	SFF-450 HNRC/HCAC	Panels	24 x 24 x 3/4	0.75	38	70%	—	12	48	54	20
		SFF-490 HNRC/HCAC	Panels	24 x 48 x 3/4	0.75	40	70%	—	6	48	54	20

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

PHYSICAL DATA

MATERIAL
Mineral Fiber

ASTM D1264 CLASSIFICATION
Type III, Form 1, Pattern C D

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

VOC EMISSIONS
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE
BioShield treatment included for added mold and mildew resistance.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY
10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/ceilings.



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com