

SUBMITTAL SHEET

SNAP-IN

Project Name _____

Specification Section _____

Ceiling Type _____

SUBSTRATE: .032"
ALUMINUM .040"

SIZES 12" x 24" 12" x 72" 24" x 24"
 12" x 48" 12" x 96" (Max) 24" x 48" (Max)

COLOR/FINISH Cotton White - #0280
 Natural - #7163
 Other # _____

PERFORATION PATTERN #103 #132
 #106 #201
 #115 Non-Perforated
 #119

PERF BORDER 1/4" Standard Other: _____

ACOUSTICAL BACKER Black Non-Woven
 Black Polywrapped Pad
 None

ACOUSTICAL RATING _____ (NRC)

TRIM Wall Angle
 Other _____

CUT-OUTS Square, Size: _____
 Round, Diameter: _____

EXPOSURE Interior Only


To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
www.CertainTeed.com/Architectural

ARCHITECTURAL

CertainTeed
SAINT-GOBAIN

PERFORATIONS & BORDERS

Perforated panels improve acoustical performance as well as create aesthetic effects.



SOUND ABSORPTION (NRC) SUMMARY*

Sound absorption can be achieved by the addition of backing ceiling panels with acoustical fabric or pad.

Perforation Pattern	% Open Area	Acoustical Infill	NRC
#103	20%	Non-Woven Acoustic Non-Woven Acoustic and 1" - 1.5 pcf Polywrapped Fiberglass	0.80 0.90
#106	16%	Non-Woven Acoustic Non-Woven Acoustic and 1" - 1.5 pcf Polywrapped Fiberglass	0.75 0.85
#115	12%	Non-Woven Acoustic Non-Woven Acoustic and 1.5" - 1.5 pcf Polywrapped Fiberglass 1.5" - 1.5 pcf Polywrapped Fiberglass	0.65 0.95 0.90
#119	8%	Non-Woven Acoustic Non-Woven Acoustic and 1" - 1.5 pcf Polywrapped Fiberglass	0.70 0.75
#132	20%	Non-Woven Acoustic Non-Woven Acoustic and 1" - 1.5 pcf Polywrapped Fiberglass	0.75 0.90
#201	19.6%	Non-Woven Acoustic Non-Woven Acoustic and 1" - 1.5 pcf Polywrapped Fiberglass	0.75 0.75

* Acoustical tests performed in accordance with ASTM C423 and E795, in a type E400 mounting. Test reports available upon request.

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50

Weight: Varies 0.75 - 1.0 lbs./sq.ft.

Wind load: N/A

Recycled content: Up to 85%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81