

M215—MICROINVERTER



The Enphase® M215 Microinverter with integrated ground delivers increased energy harvest and reduces design and installation complexity with its all-AC approach. With the advanced M215, the DC circuit is isolated and insulated from ground, so **no Ground Electrode Conductor (GEC) is required for the microinverter**. This further simplifies installation, enhances safety, and saves on labor and material costs.

The Enphase M215 integrates seamlessly with the Engage® Cable, the Envoy® Communications Gateway™ and Enlighten® — Enphase's monitoring and analysis software.

PRODUCTIVE

- Maximizes energy production
- Minimizes impact of shading, dust and debris
- No single point of system failure

SIMPLE

- No GEC needed for microinverter
- No DC design or string calculation required
- Easy installation with Engage Cable

RELIABLE

- More than 1 million hours of testing and millions of units shipped
- Industry-leading warranty — up to 25 years

M215 — MICROINVERTER TECHNICAL DATA

Input Data (DC)

M215-60-2LL-IG-S22/S23/S24

Recommended input power (STC)	190–270 W
Maximum input DC voltage	48 V
Peak power tracking voltage	27 V–39 V
Operating range	16 V–48 V
Min/Max start voltage	22 V/48 V
Max DC short circuit current	15 A
Max input current	10 A

Output Data (AC)

@208 Vac

@240 Vac

Peak output power	225 W	225 W
Rated (continuous) output power	215 W	215 W
Nominal output current	1.1 A (A rms at nominal duration)	0.9 A (A rms at nominal duration)
Nominal voltage/range	208 V/183-229 V	240 V/211-264 V
Nominal frequency/range	60.0/57–61 Hz	60.0/57–61 Hz
Extended frequency range*	57–62.5 Hz	57–62.5 Hz
Power factor	>0.95	>0.95
Maximum units per 20 A branch circuit	25 (three phase)	17 (single phase)
Maximum output fault current	850 mA rms for 6 cycles	850 mA rms for 6 cycles

Efficiency

CEC weighted efficiency, 240 VAC	96.5%
CEC weighted efficiency, 208 VAC	96.5%
Peak inverter efficiency	96.5%
Static MPPT efficiency (weighted, reference EN50530)	99.4%
Nighttime power consumption	65 mW max

Mechanical Data

Ambient temperature range	-40°C to +65°C
Operating temperature range (internal)	-40°C to +85°C
Dimensions (WxHxD)	163 mm x 173 mm x 25 mm (without mounting bracket)
Weight	1.6 kg (3.4 lbs.)
Cooling	Natural convection — no fans
Enclosure environmental rating	Outdoor — NEMA 6

Features

Compatibility	Compatible with 60-cell PV modules
Communication	Power line
Integrated ground	The DC circuit meets the requirements for ungrounded PV arrays in NEC 690.35. Equipment ground is provided in the Engage Cable. No additional GEC or ground is required. Ground fault protection is integrated into the microinverter.
Monitoring	Enlighten Manager and MyEnlighten monitoring options
Compliance	UL 1741/IEEE 1547, FCC Part 15 Class B, CAN/CSA-C22.2 NO. 0-M91, 0.4-04 and 107.1-01

*Frequency ranges can be extended beyond nominal if required by the utility.



ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE
 GYPSUM • CEILINGS • INSULATION

www.certainteed.com <http://blog.certainteed.com>

CertainTeed Corporation
 P.O. Box 860
 Valley Forge, PA 19482

Professional: 800-233-8990
 Consumer: 800-782-8777

© 02/14 CertainTeed Corporation, Printed in the U.S.A.
 Code No. 20-20-3394

