

# SYMPHONY® m Rx | SYMPHONY® m Rx High NRC

Smooth  
Mineral Fiber

The Symphony m Rx line provides a white, clean, monolithic ceiling visual. Design with other products in the Symphony Rx line for acoustical solutions.



Photo: ©Geoff Lyons


## APPLICATIONS

- Patient Rooms / Nurses' Stations
- Emergency / Treatment Rooms
- Lavatories and Restrooms
- Semi-Restricted Surgical Areas
- Corridors
- Kitchen / Food Prep Areas
- Other Commercial Buildings / Space Applications


## FEATURES AND BENEFITS

- Excellent sound absorption (NRC 0.70-0.80) and sound blocking (CAC 35-42)
- Outstanding acoustical value, high light reflectance and humidity resistance
- Exceptional durability
- Superior stain resistance and water repellency
- Tested to 2,000 wash cycles and compatible with most sanitizing solutions
- Satisfies USDA/FSIS guidelines for sanitary applications (commercial kitchens)
- Exceeds FGI guidelines for cleanability and acoustic performance in most healthcare applications
- Suited as clean room component to ISO Class 3 (highest among comparable products)
- High USDA Certified Biobased content at 98%
- Declare Label / LBC Red List Free


## SUSPENSION SYSTEM OPTIONS




Trim  
15/16 Grid



Reveal  
15/16 Grid



Narrow Reveal  
9/16 Grid



Narrow Reveal  
9/16 Grid Bolt Slot

## LEED® v4

RECYCLED CONTENT 62%

- ✓ EA: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.



EPD Available



HPD Available

# SYMPHONY® m Rx | SYMPHONY® m Rx High NRC

Smooth  
Mineral Fiber

All products in this line feature these attributes:



SAG RESISTANT



BIOSHIELD® MOLD/MILDEW RESISTANT



LR 0.90



WASHABLE w/SANITIZING CHEMICALS



EPD AVAILABLE



HPD AVAILABLE



EMISSION COMPLIANT CERTIFIED



RECYCLED CONTENT 62%

## SYMPHONY m Rx High NRC

	Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
<b>TRIM</b>											
	NRC 80	1222-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%*	14	56	64	16
		1220-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%*	8	64	74	14
<b>REVEAL</b>											
	NRC 80	1222B-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%*	14	56	64	16
		1220B-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%*	8	64	74	14
<b>NARROW REVEAL</b>											
	NRC 80	1222F-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%*	14	56	64	16
		1220F-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%*	8	64	74	14

\*Manufacturer certified pending independent confirmation

## SYMPHONY m Rx

	Format	Dimensions (in.)	NRC	CAC	Recycled Content	Pieces/carton	Sq. Ft./carton	Lbs./carton	Cartons/pallet		
<b>TRIM</b>											
	NRC 75	1222-75-RXS-1	Panels	24 x 24 x 3/4	0.75	36	62%	14	56	47	20
		1220-75-RXS-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	64	16
	NRC 70	1222-RXS-1	Panels	24 x 24 x 3/4	0.70	33	62%	14	56	47	20
		1220-RXS-1	Panels	24 x 48 x 3/4	0.70	35	62%	8	64	64	16
<b>REVEAL</b>											
	NRC 75	1222B-75-RXS-1	Panels	24 x 24 x 3/4	0.75	36	62%	14	56	56	16
		1220B-75-RXS-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	64	16
	NRC 70	1222B-RXS-1	Panels	24 x 24 x 3/4	0.70	33	62%	14	56	56	16
		1220B-RXS-1	Panels	24 x 48 x 3/4	0.70	35	62%	8	64	64	16
<b>NARROW REVEAL</b>											
	NRC 75	1222F-75-RXS-1	Panels	24 x 24 x 3/4	0.75	36	62%	14	56	56	16
		1220F-75-RXS-1	Panels	24 x 48 x 3/4	0.75	36	62%	8	64	64	16
	NRC 70	1222F-RXS-1	Panels	24 x 24 x 3/4	0.70	33	62%	14	56	56	16
		1220F-RXS-1	Panels	24 x 48 x 3/4	0.70	35	62%	8	64	64	16

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

## SYMPHONY m Rx ACCESSORIES

	Product Name	Pieces/carton	Use
	1170-SEL-1 Mineral Fiber Edge Sealant	1	For re-sealing cut edges; 1 quart container

# SYMPHONY® m Rx | SYMPHONY® m Rx High NRC

Smooth  
Mineral Fiber

## PHYSICAL DATA

**MATERIAL**  
Mineral Fiber

**ASTM E1264 CLASSIFICATION**  
Type IV, Form 2, Pattern E

**FIRE CLASS (ASTM E1264)**  
All are Class A per ASTM E84 & CAN S102  
Flame Spread: 25 or less  
Smoke Developed: 50 or less

**VOC EMISSIONS**  
Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

**MOLD/MILDEW RESISTANCE**  
BioShield® treatment included for added mold and mildew resistance.

**MAINTENANCE**  
Wash tested to 2,000+ cycles. Cleanable with sanitizing chemicals.

**WARRANTY**  
10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/ceilings](http://certainteed.com/ceilings).



## CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM  
20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](http://certainteed.com)