



Smooth fabric surface envelopes fiberglass panel and offers outstanding sound performance.

FEATURES AND BENEFITS

- Smooth, Texona fabric surface texture
- Use as a complement and/or alternative to accoustical ceiling panels for excellent performance within a space
- Attractive non-directional fissured pattern to aid in quick installation
- Available in 14 colors
- Moisture resistant

ATTRIBUTES



RECYCLED
CONTENT



MOLD/MILDEW
RESISTANT
INHERENT



LR 0.81
(SEA SALT)

LEED® v4

RECYCLED CONTENT	53%	
	PRE: 0%	POST: 53%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.


**CERTIFICATIONS &
PRODUCT DECLARATIONS**



EPD AVAILABLE

ECOPHON® AKUSTO™ WALL C TEXONA









COLORS



AKUSTO WALL C TEXONA PANELS


WALL PANEL		COLOR	DIMENSIONS MM (IN.)	NRC	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. M (FT.)/ CARTON	LBS./ CARTON	
	NRC .95	3557 1002	Garlic	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.52	53%	4	21.3 (≈ 70)	71
		3557 1004	Pepper	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.17	53%	4	21.3 (≈ 70)	71
		3557 1005	Licorice	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.05	53%	4	21.3 (≈ 70)	71
		3557 1011	Ginger	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.56	53%	4	21.3 (≈ 70)	71
		3557 1056	Oyster	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.32	53%	4	21.3 (≈ 70)	71
		3557 1060	Sea Salt	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.81	53%	4	21.3 (≈ 70)	71
		3557 1064	Acai	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.11	53%	4	21.3 (≈ 70)	71
		3557 1065	Thyme	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.47	53%	4	21.3 (≈ 70)	71
		3557 1066	Poppyseed	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.28	53%	4	21.3 (≈ 70)	71
		3557 1081	Goji	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.27	53%	4	21.3 (≈ 70)	71
		3557 1082	Peach	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.55	53%	4	21.3 (≈ 70)	71
		3557 1083	Sage	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.40	53%	4	21.3 (≈ 70)	71
		3557 1080	Eucalyptus	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.23	53%	4	21.3 (≈ 70)	71
		3557 1084	Scallop	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.76	53%	4	21.3 (≈ 70)	71

ACCESSORIES

AKUSTO WALL C TEXONA ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE	
	2630 0214	Connect Fixing Bracket	260	For direct fixing of Connect WP Profile to structure
	2631 1050	Connect WP Space Bar (Galvanized)	10	For use in conjunction with WP Profile when Akusto Wall C panels are installed vertically
	2631 1051	Connect WP Profile Connect (White 03)	8	Installed on walls and provides channel into which Akusto Wall C panels are inserted
	2631 1052	Connect WP Profile (Natural 02)	8	Installed on walls and provides channel into which Akusto Wall C panels are inserted
	2631 1074	Connect WP Profile (Black 01)	8	Installed on walls and provides channel into which Akusto Wall C panels are inserted
	2631 1057	Connect WP External Corner (White 03)	4	Used in conjunction with WP Profile to create 90 degree outside corners
	2631 1058	Connect WP External Corner (Grey 02)	4	Used in conjunction with WP Profile to create 90 degree outside corners
	2631 1059	Connect WP External Corner (Black 01)	4	Used in conjunction with WP Profile to create 90 degree outside corners
	2630 0933	WP Profile Splice	4	For use when running multiple lengths of WP Profile end-to-end
	2630 0219	Connect Spline (Black)	100	For use in the kerf between Akusto Wall C panels when they are installed vertically
	2630 0132	Connect Direct Fixing Plate (Akusto Wall C)	100	For direct fixing of Akusto Wall C panels when they are installed horizontally

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

EDGE DETAILS



Kerfed Edge

PHYSICAL DATA

MATERIAL

Fiberglass

FIRE CLASS (ASTM E1264)

Tested according to ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year Ecophon Warranty.

Full warranty information can be found at certainteed.com/warranty.

