

FLINTROCK™ ROOFING GRANULES

Product Information

Product Use: Level up your aesthetic craftsmanship by broadcasting color-matched granules into side or end lap bleed out areas or liquid-applied flashing details.

Product Composition and Features: FlintRock™ Roofing Granules are tough, dense, non-porous, weather- and UV-resistant, ceramic-coated rocks used as surfacing material for roofing purposes only, #11 grade. FlintRock is manufactured with true-blend colors (not just single granule colors) to match CertainTeed low-slope membranes and steep-slope shingles.

Packaging 5G Pail
Weight 50 lbs. (40 lbs. for CoolStar® Granules)
Colors Buff, Burnt Sienna, Colonial Slate, CoolStar, Heather Blend, Hunter Green, Moiré Black, Mojave Tan, Red, Resawn Shake, Terra Cotta, Weathered Wood, White

Product Application

Transfer a manageable volume of granules into a cup or bag. Using a gloved hand, broadcast granules to refusal or rejection, completely saturating the surface of the target area.

Physical Properties

Grade #11
Moisture Content 0.3% Maximum
Color Durability Proven by long-term field performance and accelerated weathering tests
Opacity Opaque to protect the asphalt substrate from the effects of sunlight
Hardness 6.0-7.0 Moh's Mineral Scale
Bulk Density 90-96 lbs./ft.³ Packed
Specific Gravity 2.55-2.70

Storage & Disposal: No special storage requirements. Dispose of contents/container in accordance with local/regional/national/international regulations.

Warnings

Danger: May cause cancer by inhalation. Causes damage to lungs through prolonged or repeated exposure by inhalation.

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not eat, drink, or smoke when using this product. Wear safety glasses or goggles. In case of inadequate ventilation wear respiratory protection. California Proposition 65 WARNING: This product can expose you to quartz, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov

Technical Assistance and Services

CertainTeed provides technical assistance in the product selection, specification, and application guidelines for all CertainTeed commercial roof systems. Field representatives are available for consultation in each region.

For more information, contact CertainTeed Commercial Roofing Technical Services at 800-396-8134 ext. 2 or rpg@saint-gobain.com

Warranties

CertainTeed supports our low-slope roof systems with Limited (product-only) and No Dollar Limit (NDL, product and workmanship) warranties. Warranty type and duration is dependent on roof system configuration and contractor selection. Only CertainTeed Gold and Silver Star Contractors are eligible to apply for NDL warranties on specific roof projects.

For more information, see CertainTeed Commercial Roof Systems Specifications or contact Commercial Roofing Technical Services.



CertainTeed

CEILING • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM

20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com