

SUBMITTAL SHEET

HIGH PROFILE SERIES™

HORIZONTALLY CURVED

Project Name _____

Specification Section _____

Ceiling Type _____

SUBSTRATE

Extruded Aluminum

PROFILE

(Width x Height
in cm (in))

Beam

- 3.81x11.11 (1.5x4.375)
- 3.81x16.19 (1.5x6.375)
- 3.81x21.27 (1.5x8.375) (min. radius 243.81 (96))
- 5.10x20.32 (2x8) (min. radius 243.81 (96))
- 10.16x10.16 (4x4) (min. radius 243.81 (96))
- * Length - minimum 1.21 m (4'), maximum 6.10 m (20')

Aero

- 4.13x16.19 (1.625x6.375)

Open Beam

- 10.16x10.16 (4x4)
(min. radius 243.81 (96))

Other - contact manufacturer

- _____

BEAM SPACING

- 15.24 cm (6 ") 20.32 cm (8 ") 30.48 cm (12 ") Other _____

HORIZONTAL CURVATURE

Radius: _____ (Minimum 121.92 cm (48 "), except where otherwise specified)

* For multiple radii, or two radii on the same beam, contact manufacturer.

COLOUR/FINISH

Beam Finish

- Cotton White - #0280
- Natural - #7163
- Other _____

Hanger Bracket Finish

- Black
- White
- Painted to match plenum

END CAPS

- Yes No

EXPOSURE

- Interior Only

To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.233.8990
www.certainteed.ca/architectural

ARCHITECTURAL

CertainTeed
SAINT-GOBAIN

CertainTeed Architectural Products, a division of CertainTeed Canada, Inc.

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year Limited Warranty

Seismic rating: Classes A,B,C,D,E,F

Fire rating: Rated per CAN/ULC-S102

- Painted or anodized metal: Flame spread: ≤ 25 , Smoke ≤ 50

Weight: Varies 9.76 - 19.53 kg/m² (2.0 - 4.0 lbs./sq.ft.)

Wind load: N/A

Recycled content: Minimum of 50%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81