

# SUBMITTAL SHEET

# TORSION SPRING

# - EXTERIOR

Project Name \_\_\_\_\_

Specification Section \_\_\_\_\_

Ceiling Type \_\_\_\_\_

**SUBSTRATE:** **ALUMINUM**       .040"       .050"       .063"

**SIZES**       24" x 24"     30" x 30"  
 24" x 48"     30" x 60"     Other: \_\_\_\_\_

(Other sizes available; length/width may be limited by perforation selection, consult CertainTeed for details.)

**COLOR/FINISH**       Cotton White - #0280       Natural - #7163  
 Other #: \_\_\_\_\_

**PERFORATION PATTERN**      Contact CertainTeed for details

**ACOUSTICAL BACKER**       Black Polywrapped Pad  
 None

**TRIM**       Wall Angle  
 Other: \_\_\_\_\_  
  
Color/Finish # \_\_\_\_\_

**CUT-OUTS**       Square, Size: \_\_\_\_\_  
 Round, Diameter: \_\_\_\_\_

**EXPOSURE**       Exterior - Design Wind Pressure (required) \_\_\_\_\_ PSF

Shop Drawings required on all Exterior projects

**To Contact Us:**  
5015 Oakbrook Parkway, Suite 100  
Norcross, GA 30093  
phone: 800.366.4327  
fax: 770.806.0214  
www.certainteed.com/architectural

**ARCHITECTURAL**

**CertainTeed**  
SAINT-GOBAIN

# SUBMITTAL SHEET **TORSION SPRING - EXTERIOR**

## PHYSICAL DATA

---

**Substrate:** Aluminum

**Warranty:** 1 year Limited Warranty

**Seismic rating:** Zones A,B,C,D,E,F

**Fire rating:** Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread:  $\leq 25$ , Smoke  $\leq 50$

Class A Fire Rated per CAN/ULC-S102

- Painted or anodized metal: Flame spread:  $\leq 25$ , Smoke  $\leq 50$

**Weight:** Varies 1.0 - 1.5 lbs./sq.ft.

**Wind load:** Per code (for exterior applications)

**Recycled content:** Up to 85%

**Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:**

- Cotton White: LR = 0.81

---

**For technical details, go to [certainteed.com/architectural](https://certainteed.com/architectural) • 800.366.4327**