

A mineral fiber panel with high impact resistance and high light reflectance, ideal in educational settings.

**FEATURES AND BENEFITS**

- Up to 25% higher surface hardness than conventional wet-felted ceiling products per ASTM C 367 testing
- Environmental Product Declaration (EPD) available for this product
- Available in (Protectone) version suited for fire assemblies
- Shares surface pattern with other Fine Fissured products
- Health Product Declaration (HPD) available for this product

**ATTRIBUTES**



SAG  
RESISTANT



BIOSHIELD®  
MOLD/MILDEW  
RESISTANT



LR 0.84



RECYCLED  
CONTENT  
33-44%



EMISSION  
COMPLIANT  
CERTIFIED

**LEED® v4**

RECYCLED CONTENT		
CLASS A PROTECTONE®	33%	
	PRE: 28%	POST: 5%
	44%	
	PRE: 42%	POST: 2%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

**CERTIFICATIONS & PRODUCT DECLARATIONS**




EPD AVAILABLE




HPD AVAILABLE

## EDGE DETAILS



Trim  
9/16" EZ Stab  
Elite Narrow



Trim  
15/16" EZ Stab  
Classic

## SCHOOL BOARD

	FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET		
<b>TRIM</b>												
	NRC .55	FFSB-157	Panels	24 x 24 x 5/8	0.55	35	33%	—	16	64	47	20
		FFSB-197	Panels	24 x 48 x 5/8	0.55	35	33%	—	8	64	47	20
		PFFSB-157	Panels	24 x 24 x 5/8	0.55	35	44%	Yes*	16	64	72	20
		PFFSB-197	Panels	24 x 48 x 5/8	0.55	40	44%	Yes*	8	64	72	20

\* Protectone\*: A fire-resistive ceiling when used in applicable UL/ULC assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.

**CAN'T FIND A SIZE?** Contact your local Sales Representative or call 800-233-8990

## PHYSICAL DATA

### MATERIAL

Mineral Fiber

### ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C E

### FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

### VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

### MOLD/MILDEW RESISTANCE

BioShield treatment included for added mold and mildew resistance.

### MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

### WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/warranty](http://certainteed.com/warranty).



## CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS  
20 Moores Road, Malvern, PA 19355 800-366-4327 [certainteed.com/architectural](http://certainteed.com/architectural)