

# SUBMITTAL SHEET

# TORSION SPRING

# - EXTERIOR

Project Name \_\_\_\_\_

Specification Section \_\_\_\_\_

Ceiling Type \_\_\_\_\_

**SUBSTRATE:**  
**ALUMINUM**

1.02 mm (.040")     1.27 mm (.050")     1.60 mm (.063")

**SIZES**

60.96 cm x 60.96 cm (24" x 24")     76.2 cm x 76.2 cm (30" x 30")  
 60.96 cm x 121.92 cm (24" x 48")     76.2 cm x 152.4 cm (30" x 60")  
 Other: \_\_\_\_\_

(Other sizes available; length/width may be limited by perforation selection, consult CertainTeed for details.)

**COLOUR/FINISH**

Cotton White - #0280     Natural - #7163  
 Other #: \_\_\_\_\_

**PERFORATION PATTERN**

Contact CertainTeed for details

**ACOUSTICAL BACKER**

Black Polywrapped Pad  
 None

**TRIM**

Wall Angle  
 Other: \_\_\_\_\_

Colour/Finish # \_\_\_\_\_

**CUT-OUTS**

Square, Size: \_\_\_\_\_  
 Round, Diameter: \_\_\_\_\_

**EXPOSURE**

Exterior - Design Wind Pressure (required) \_\_\_\_\_ PSF (Pascals)

Shop Drawings required on all Exterior projects.

**To Contact Us:**

5015 Oakbrook Parkway, Suite 100  
Norcross, GA 30093  
phone: 800.233.8990  
www.certainteed.ca/architectural

ARCHITECTURAL

**CertainTeed**  
SAINT-GOBAIN

CertainTeed Architectural Products, a division of CertainTeed Canada, Inc.

# SUBMITTAL SHEET **TORSION SPRING - EXTERIOR**

## PHYSICAL DATA

---

**Substrate:** Aluminum

**Warranty:** 1 year Limited Warranty

**Seismic rating:** Classes A,B,C,D,E,F

**Fire rating:** Rated per CAN/ULC-S102

- Painted or anodized metal: Flame spread:  $\leq 25$ , Smoke  $\leq 50$

**Weight:** Varies 4.88 - 7.32 kg/m<sup>2</sup> (1.0 - 1.5 lbs./sq.ft.)

**Wind load:** Per code (for exterior applications)

**Recycled content:** Up to 85%

**Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:**

- Cotton White: LR = 0.81

---

For technical details, go to [certainteed.ca/architectural](https://certainteed.ca/architectural) • 800.233.8990